

R O W A N

Salzburg

by Martin Storey



YARN

	S	M	L	XL	
To fit bust	81-86	91-97	102-107	112-117	cm
	32-34	36-38	40-42	44-46	in

Rowan Pure Wool Aran

17 19 21 23 x 100gm

(photographed in Antique Red 693)

NEEDLES

1 pair 4mm (no 8) (US 6) needles
1 pair 4½mm (no 7) (US 7) needles
4mm (no 8) (US 6) circular needle

FASTENINGS - 11 x 00410 buttons and 3 x 5 cm buckles

TENSION

29 sts and 25 rows to 10 cm measured over patt using 4½mm(US 7) needles.

BACK

Using 4mm (US 6) needles cast on 147 [161: 179: 197] sts.

Row 1 (RS): K2 [1: 2: 1], *P1, K1, rep from * to last 1 [0: 1: 0] st, K1 [0: 1: 0].

Row 2: K1, P1 [0: 1: 0], *K1, P1, rep from * to last 1 [2: 1: 2] st, K1 [2: 1: 2].

These 2 rows form patt.

Work in patt for a further 2 rows, ending with RS facing for next row.

Change to 4½mm (US 7) needles.

Cont in patt until back meas 43 [44: 45: 46] cm, ending with

RS facing for next row.

Shape back belt slot

Next row (RS): Patt 64 [71: 80: 89] sts and turn, leaving rem sts on a holder.

Work on this set of sts only for right back panel.

Cast on 3 sts at beg of next row, taking cast-on sts into rib. 67 [74: 83: 92] sts.

Work 10 rows, ending with RS facing for next row.

Next row (RS): Patt to last 3 sts, cast off rem 3 sts.

Break yarn and leave rem 64 [71: 80: 89] sts on a 2nd holder. Return to sts left on first holder, rejoin yarn with RS facing, K2, (P1, K1) 8 times, K1 and turn, leaving rem sts on first holder.

Work on this set of 19 sts only for centre panel.

Next row (WS): K1, (P1, K1) 9 times.

Keeping sts correct as now set, work a further 11 rows, ending with WS facing for next row.

Break yarn and leave these 19 sts on a 3rd holder.

Return to sts left on first holder, rejoin yarn with RS facing, cast on 3 sts (taking cast-on sts into rib), patt to end. 67 [74: 83: 92] sts.

Work on this set of sts only for left back panel.

Work 11 rows, ending with RS facing for next row.

Next row (RS): Cast off 3 sts, patt to end.

64 [71: 80: 89] sts.

Join sections

Next row (WS): Patt 64 [71: 80: 89] sts of left back panel, then patt 19 sts of centre panel, then patt 64 [71: 80: 89] sts of right back panel. 147 [161: 179: 197] sts.

Cont straight until back meas 61 [62: 63: 64] cm, ending with

RS facing for next row.

Shape armholes

Keeping patt correct, cast off 6 sts at beg of next 2 rows.

135 [149: 167: 185] sts.

Dec 1 st at each end of next and foll 4 alt rows.

125 [139: 157: 175] sts.

Cont straight until armhole meas 25 [26: 27: 28] cm, ending with RS facing for next row.

Shape shoulders and back neck

Cast off 12 [14: 17: 20] sts at beg of next 2 rows.

101 [111: 123: 135] sts.

Next row (RS): Cast off 12 [14: 17: 20] sts, patt until there are 16 [19: 21: 24] sts on right needle and turn, leaving rem sts on a holder.

Work each side of neck separately.

Cast off 4 sts at beg of next row.

Cast off rem 12 [15: 17: 20] sts.

With RS facing, rejoin yarn to rem sts, cast off centre 45 [45: 47: 47] sts, patt to end.

Complete to match first side, reversing shapings.

LOWER POCKET FLAPS (make 2)

Using 4½mm (US 7) needles cast on 43 sts.

Row 1 (RS): K2, *P1, K1, rep from * to last st, K1.

Row 2: K1, *P1, K1, rep from * to end.

These 2 rows form patt.

Work in patt for a further 15 rows, ending with **WS** facing for next row.

Row 18 (WS): P2tog tbl, patt to last 2 sts, P2tog.

Break yarn and leave rem 41 sts on a holder.

UPPER POCKET FLAPS (make 2)

Using 4½mm (US 7) needles cast on 37 sts.

Beg with row 1, work in patt as given for lower pocket flaps for 17 rows, ending with **WS** facing for next row.

Row 18 (WS): P2tog tbl, patt to last 2 sts, P2tog.

Break yarn and leave rem 35 sts on a holder.

LEFT FRONT

Using 4mm (US 6) needles cast on 75 [82: 91: 100] sts.

Row 1 (RS): K2 [1: 2: 1], *P1, K1, rep from * to last st, K1.

Row 2: *K1, P1, rep from * to last 1 [2: 1: 2] st, K1 [2: 1: 2].

These 2 rows form patt.

Work in patt for a further 2 rows, ending with RS facing for next row.

Change to 4½mm (US 7) needles.

Cont straight until left front meas 38 [39: 40: 41] cm, ending with RS facing for next row.

Place lower pocket flap

Next row (RS): Patt 17 [20: 25: 30] sts, holding WS of first lower pocket flap against RS of left front, patt tog first st of flap with next st of front, (patt tog next st of flap with next st of front) 40 times, patt 17 [21: 25: 29] sts.

Cont straight until left front matches back to beg of armhole shaping, ending with RS facing for next row.

Shape armhole

Keeping patt correct, cast off 6 sts at beg of next row. 69 [76: 85: 94] sts.

Work 1 row.

Dec 1 st at armhole edge of next and foll 4 alt rows. 64 [71: 80: 89] sts.

Work 1 row, ending with RS facing for next row.

Place upper pocket flap

Next row (RS): Patt 12 [15: 20: 25] sts, holding WS of first upper pocket flap against RS of left front, patt tog first st of flap with next st of front, (patt tog next st of flap with next st of front) 34 times, patt 17 [21: 25: 29] sts.

Cont straight until 31 [31: 33: 33] rows less have been worked than on back to beg of shoulder shaping, ending with **WS** facing for next row.

Shape neck

Keeping patt correct, cast off 12 sts at beg of next row. 52 [59: 68: 77] sts.

Dec 1 st at neck edge of next 7 rows, then on foll 7 [7: 8: 8] alt rows, then on 2 foll 4th rows. 36 [43: 51: 60] sts.

Work 1 row, ending with RS facing for next row.

Shape shoulder

Cast off 12 [14: 17: 20] sts at beg of next and foll alt row.

Work 1 row.

Cast off rem 12 [15: 17: 20] sts.

Mark positions for 5 buttons along left front opening edge – first to come in row 69, last to come 2 cm below neck shaping, and rem 3 buttons evenly spaced between.

RIGHT FRONT

Using 4mm (US 6) needles cast on 75 [82: 91: 100] sts.

Row 1 (RS): K2, *P1, K1, rep from * to last 1 [0: 1: 0] st, K1 [0: 1: 0].

Row 2: K1, P1 [0: 1: 0], *K1, P1, rep from * to last st, K1.

These 2 rows form patt.

Work in patt for a further 2 rows, ending with RS facing for next row.

Change to 4½mm (US 7) needles.

Cont in patt for a further 64 rows, ending with RS facing for next row.

Next row (buttonhole row) (RS): Patt 7 sts, cast off 3 sts (to make a buttonhole – cast on 3 sts over these cast-off sts on next row), patt to end.

Working a further 4 buttonholes in this way to correspond with positions marked for buttons on left front and noting that no further reference will be made to buttonholes, cont as folls:

Cont straight until right front meas 38 [39: 40: 41] cm, ending with RS facing for next row.

Place lower pocket flap

Next row (RS): Patt 17 [21: 25: 29] sts, holding WS of second lower pocket flap against RS of right front, patt tog

first st of flap with next st of front, (patt tog next st of flap with next st of front) 40 times, patt 17 [20: 25: 30] sts.

Cont straight until right front matches back to beg of armhole shaping, ending with **WS** facing for next row.

Shape armhole

Keeping patt correct, cast off 6 sts at beg of next row.

69 [76: 85: 94] sts.

Dec 1 st at armhole edge of next and foll 4 alt rows.

64 [71: 80: 89] sts.

Work 1 row, ending with RS facing for next row.

Place upper pocket flap

Next row (RS): Patt 17 [21: 25: 29] sts, holding WS of second upper pocket flap against RS of right front, patt tog first st of flap with next st of front, (patt tog next st of flap with next st of front) 34 times, patt 12 [15: 20: 25] sts.

Complete to match left front, reversing shapings.

SLEEVES

Using 4mm (US 6) needles cast on 111 [113: 115: 115] sts.

Row 1 (RS): K0 [1: 0: 0], *P1, K1, rep from * to last 1 [0: 1: 1] st, P1 [0: 1: 1].

Row 2: P0 [1: 0: 0], *K1, P1, rep from * to last 1 [0: 1: 1] st, K1 [0: 1: 1].

These 2 rows form patt.

Work in patt for a further 2 rows, ending with RS facing for next row.

Change to 4½mm (US 7) needles.

Cont in patt, shaping sides by inc 1 st at each end of next and 2 foll 4th rows, taking inc sts into patt. 117 [119: 121: 121] sts.

Work 3 rows, ending with RS facing for next row.

Shape belt slots

Next row (RS): (Inc in first st) 0 [1: 1: 1] times, patt 17 [17: 18: 18] sts and turn, leaving rem sts on a holder.

Work on this set of sts only for first side panel.

Cast on 2 sts at beg of next row, taking cast-on sts into rib.

19 [21: 22: 22] sts.

Work 10 rows, inc 1 st at beg of next [3rd: 3rd: 3rd] and every foll 6th [4th: 4th: 4th] row and ending with RS facing for next row. 21 [23: 24: 24] sts.

Next row (RS): (Inc in first st) 0 [1: 1: 1] times, patt to last 2 sts, cast off rem 2 sts.

Break yarn and leave rem 19 [22: 23: 23] sts on a 2nd holder.

**Return to sts left on first holder, rejoin yarn with RS facing, K2, (P1, K1) twice, K1 and turn, leaving rem sts on first holder.

Work on this set of 7 sts only for first belt loop.

Next row (WS): K1, (P1, K1) 3 times.

Keeping sts correct as now set, work a further 11 rows, ending with **WS** facing for next row.

Break yarn and leave these 7 sts on a 3rd holder.***

Return to sts left on first holder, rejoin yarn with RS facing, cast on 2 sts, patt 31 sts. 33 sts.

Work on this set of sts only for first centre panel.

Cast on 2 sts at beg of next row. 35 sts.

Work 10 rows, ending with RS facing for next row.

Next row (RS): Cast off 2 sts, patt to last 2 sts, cast off rem

2 sts.

Break yarn and leave rem 31 sts on a 4th holder.**

Rep from ** to ** to form second belt loop and second centre panel.

Now rep from ** to *** to form third belt loop.

Return to sts left on first holder, rejoin yarn with RS facing, cast on 2 sts, patt to last 0 [1: 1: 1] st, (inc in last st) 0 [1: 1: 1] times. 19 [21: 22: 22] sts.

Work on this set of sts only for second side panel.

Work 11 rows, inc 1 st at end of 2nd [4th: 4th: 4th] and every foll 6th [4th: 4th: 4th] row and ending with RS facing for next row. 21 [23: 24: 24] sts.

Next row (RS): Cast off 2 sts, patt to last 0 [1: 1: 1] st, (inc in last st) 0 [1: 1: 1] times. 19 [22: 23: 23] sts.

Join sections

Next row (WS): Patt 19 [22: 23: 23] sts of second side panel, 7 sts of 3rd belt loop, 31 sts of 2nd centre panel, 7 sts of 2nd belt loop, 31 sts of first centre panel, 7 sts of first belt loop, then 19 [22: 23: 23] sts of first side panel.

121 [127: 129: 129] sts.

Cont in patt, shaping sides by inc 1 st at each end of next [3rd: 3rd: 3rd] and every foll 6th [6th: 4th: 4th] row to 145 [151: 141: 159] sts, then on every foll - [-: 6th: 6th] row until there are - [-: 157: 163] sts, taking inc sts into patt.

Cont straight until sleeve meas 43 [44: 45: 45] cm, ending with RS facing for next row.

Shape top

Keeping patt correct, cast off 6 sts at beg of next 2 rows.

133 [139: 145: 151] sts.

Dec 1 st at each end of next and foll 4 alt rows, then on foll row, ending with RS facing for next row.

Cast off rem 121 [127: 133: 139] sts.

MAKING UP

Press.

Join both shoulder seams using back stitch, or mattress stitch if preferred.

Collar

Using 4mm (US 6) circular needle cast on 257 [257: 265: 265] sts.

Row 1 (RS): K1, *P1, K1, rep from * to end.

Row 2: P1, *K1, P1, rep from * to end.

These 2 rows form patt.

Work in patt for a further 1 row, ending with **WS** facing for next row.

Row 4 (WS): Cast off 60 sts, patt to last 60 sts, cast off last 60 sts. Break yarn.

Change to 4½mm (US 7) needles.

Rejoin yarn to centre 137 [137: 145: 145] sts with RS facing and cont as folls:

Inc 1 st at each end of next 5 rows, taking inc sts into patt. 147 [147: 155: 155] sts.

Cont straight until collar meas 18 cm from cast-on edge, ending with RS facing for next row.

Cast off in rib.

Slip stitch cast-off edges of first 4 rows to row-end edges of main section of collar.

Epaulettes (make 2)

Using 4½mm (US 7) needles cast on 11 sts.

Work in patt as given for pocket flaps for 12 [14: 16: 18] cm, ending with RS facing for next row.

Next row (RS): K2, K2tog, P1, K1, P1, K2tog tbl, K2. 9 sts.

Next row: K1, P1, P2tog, P1, P2tog tbl, P1, K1. 7 sts.

Next row: K2, sl 1, K2tog, pss0, K2. 5 sts.

Next row: K1, P3tog, K1. 3 sts.

Next row: sl 1, K2tog, pss0 and fasten off.

Epaulette strips (make 2)

Using 4½mm (US 7) needles cast on 7 sts.

Work in patt as given for pocket flaps for 5 cm, ending with RS facing for next row.

Cast off.

Lay epaulettes over shoulder seams, matching cast-on edge to neck edge and sew together at neck edge. Attach button through shaped end of epaulette and shoulder seam as in photograph. Lay epaulette strip over epaulette near button and sew in place as in photograph. Sew cast-off edge of collar to neck edge, matching cast-on edges of first 4 rows to front opening edges and enclosing epaulettes in seam.

See information page for finishing instructions, setting in sleeves using the shallow set-in method. On inside, neatly sew down cast-on and cast-off edges behind belt slots. Sew buttons onto pocket flaps as in photograph, attaching flaps to fronts at

same time.

Belt

Using 4½mm (US 7) needles cast on 15 sts.

Work in patt as given for pocket flaps for 115 [125: 135: 145] cm, ending with RS facing for next row.

Shape end

Row 1 (RS): K2, K2tog, patt to last 4 sts, K2tog tbl, K2.

Row 2: K1, P1, P2tog, patt to last 4 sts, P2tog tbl, P1, K1.

Rows 3 and 4: As rows 1 and 2. 7 sts.

Row 5: K2, sl 1, K2tog, pss0, K2. 5 sts.

Row 6: K1, P3tog, K1. 3 sts.

Row 7: sl 1, K2tog, pss0 and fasten off.

Attach buckle to cast-on edge of belt, then thread belt through belt slot in back.

Sleeve belts (both alike)

Using 4½mm (US 7) needles cast on 15 sts.

Work in patt as given for pocket flaps for 50 [51: 52: 52] cm, ending with RS facing for next row.

Shape end

Row 1 (RS): K2, K2tog, patt to last 4 sts, K2tog tbl, K2.

Row 2: K1, P1, P2tog, patt to last 4 sts, P2tog tbl, P1, K1.

Rows 3 and 4: As rows 1 and 2. 7 sts.

Row 5: K2, sl 1, K2tog, pss0, K2. 5 sts.

Row 6: K1, P3tog, K1. 3 sts.

Row 7: sl 1, K2tog, pss0 and fasten off.

Attach buckle to cast-on edge of belt, then thread belt through belt slots in sleeve as in photograph.

